



121814

**APPLICATION**

- Single meter positions
- Designed to receive watthour positions that meet ANSI C12.10
- Combination CT/meter enclosure
- Overhead or underground feed

**CONSTRUCTION**

- Type 3R construction
- Removable test switch perch
- CT mounting base provision
- H-base hub provision – overhead only
- Ring style
- Snap type sealing ring included
- Cover has newly designed fixed handles (not shown)

**STANDARDS**

- UL 414 listed, complies with ANSI C12.7

**FINISH**

- ANSI 61 gray acrylic electrocoat finish

**ACCESSORIES**

- Screw type sealing ring — catalog #25016D
- H-base hubs
- Steel or clear lexan covers for socket openings
- CT mounting bases
- 5th jaw kit — catalog #50371

**Overhead/Underground-Surface Mount**

CATALOG NUMBER	MAIN DISCONNECT	AMPACITY MAX.	AMPACITY CONT.	VOLTAGE	SERVICE TYPE	NUMBER OF JAWS	HUB PROV.	CONDUCTOR LUG RANGE		FIGURE NUMBER	DIMENSIONS (INCHES)			
								ALL TERMINALS	GROUNDING TERMINAL		HEIGHT (H)	WIDTH (W)	DEPTH (D)	(L)
121814	NONE	20	20	600	1Ø	4	H	14 AWG - 10 AWG	14 AWG - 2/0 AWG	Fig. 1	42	24	11	15 11/16
121815	NONE	20	20	600	1Ø	5	H	14 AWG - 10 AWG	14 AWG - 2/0 AWG	Fig. 1	42	24	11	15 11/16
121816	NONE	20	20	600	1Ø	6	H	14 AWG - 10 AWG	14 AWG - 2/0 AWG	Fig. 1	42	24	11	15 11/16
121818	NONE	20	20	600	1Ø	8	H	14 AWG - 10 AWG	14 AWG - 2/0 AWG	Fig. 1	42	24	11	15 11/16
122013	NONE	20	20	600	3Ø	13	H	14 AWG - 10 AWG	14 AWG - 2/0 AWG	Fig. 2	42	36	11	15 11/16
122015	NONE	20	20	600	3Ø	15	H	14 AWG - 10 AWG	14 AWG - 2/0 AWG	Fig. 2	42	36	11	15 11/16
122018	NONE	20	20	600	1Ø or 3Ø	8	H	14 AWG - 10 AWG	14 AWG - 2/0 AWG	Fig. 2	42	36	11	15 11/16

**Underground-Surface Mount**

CATALOG NUMBER	MAIN DISCONNECT	AMPACITY MAX.	AMPACITY CONT.	VOLTAGE	SERVICE TYPE	NUMBER OF JAWS	HUB PROV.	CONDUCTOR LUG RANGE		FIGURE NUMBER	DIMENSIONS (INCHES)			
								ALL TERMINALS	GROUNDING TERMINAL		HEIGHT (H)	WIDTH (W)	DEPTH (D)	(L)
U121814	NONE	20	20	600	1Ø	4	NONE	14 AWG - 10 AWG	14 AWG - 2/0 AWG	Fig. 1	52	24	11	25 11/16
U121815	NONE	20	20	600	1Ø	5	NONE	14 AWG - 10 AWG	14 AWG - 2/0 AWG	Fig. 1	52	24	11	25 11/16
U121816	NONE	20	20	600	1Ø	6	NONE	14 AWG - 10 AWG	14 AWG - 2/0 AWG	Fig. 1	52	24	11	25 11/16
U121818	NONE	20	20	600	1Ø or 3Ø	8	NONE	14 AWG - 10 AWG	14 AWG - 2/0 AWG	Fig. 1	52	24	11	25 11/16
U122013	NONE	20	20	600	3Ø	13	NONE	14 AWG - 10 AWG	14 AWG - 2/0 AWG	Fig. 2	52	36	11	25 11/16
U122015	NONE	20	20	600	3Ø	15	NONE	14 AWG - 10 AWG	14 AWG - 2/0 AWG	Fig. 2	52	36	11	25 11/16
U122018	NONE	20	20	600	1Ø or 3Ø	8	NONE	14 AWG - 10 AWG	14 AWG - 2/0 AWG	Fig. 2	52	36	11	25 11/16